



A POLI-TAPE GROUP Company

## TEC FLOOR 200

### Product Information

Monomeric PVC (embossed, transparent matt, 120  $\mu$ ) with a clear solvent based acrylic adhesive (permanent), laminated on one-sided clay-coated silicone paper liner (90 g/m<sup>2</sup>).

The PVC offers an excellent dimensional stability.

Especially designed for floorgraphic applications with anti-slippery character and scratch resistant surface for mid-term floor decoration and advertising (airports, railway stations, shopping centers).

### Shelf Life

2 years when stored in the original packaging between 20°C and 25°C at 50% relative humidity.

### Recommendations for laminating

Please ensure the print is perfectly dry before laminating. We suggest to let the material dry for at least 48 hours after printing.

### Safety Data Sheet

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities.

### Technical Data

Carrier:	monomeric PVC (embossed), highly stabilized, calendared
Thickness:	120 $\mu$ +/- 5 %
Adhesive:	clear solvent acrylic, permanent
Adhesion:	5,5 N/cm
Liner:	one-sided clay-coated silicone paper (90 g/m <sup>2</sup> )
Application temperature:	+10 - +40 °C
Service temperature:	- 20 - +50 °C
Outdoor durability:	3 years (For application as protection film) 6 months (For application as floorgraphic-film with anti-slippery character)

### Standard Dimensions

1050 mm x 50 m

1370 mm x 50 m

1550 mm x 50 m

#### KEMICA S.r.l.

Via F.lli Rusjan, 76 - Frazione Rupa  
34070 Savogna d'Isonzo (GO) - ITALIA

Phone: +39 0481 882 501

Fax: +39 0481 882 440

E-Mail: [info@kemicasrl.it](mailto:info@kemicasrl.it)

Internet: [www.kemica.it](http://www.kemica.it)

12/12/2012

The following technical details are issued to the best of our knowledge, however, without any responsibility for results due to several different kinds of material and application processes. Therefore, we highly recommend that before every usage a test should be conducted on the original material.